


# LED SHOP LINE

CYF SYS2 SP36W5715LM840L170WH

PRODUCT DATA



821-548



## General Information

|                                   |  |
|-----------------------------------|--|
| Order Code                        | 821-548  |
| Product Description               | CYF SYS2 SP36W5715LM840L170WH  |
| Application                       | Shops, Offices, General Indoor Lighting  |
| Installation                      | Ceiling Surfaced & Suspended with accessories  |
| Accessories                       | Shop Line Suspension Kit   |
| Luminaire type                    | Linear LED Luminaire with Opal Diffuser  |
| Light Source                      | LED modules SMD Vossloh-Schwabe  |
| Number of light sources           | 1 pc   |
| Light Source Colour               | 4000K, cool white  |
| Driver                            | Built-in Vossloh-Schwabe   |
| Dimming                           | Not Dimmable   |
| Energy Class                      | A++  |
| Optical Risk                      | RG 0   |
| Protection class                  | Class I  |
| Ingress protection code           | IP 20 [Finger-protected]   |
| Mechanical impact protection code | IK03   |
| Standards                         | 2014/30/EU Electromagnetic Compatibility Directive<br>2014/35/EU Low Voltage Directive |
| CE mark                           | Yes  |
| Warranty                          | 5 years  |

## Electrical Data

|                 |          |
|-----------------|----------|
| Input Power     | 40 W     |
| Input voltage   | 220-240V |
| Input Frequency | 50-60 Hz |
| Drive Current   | 350 mA   |
| Power Factor    | 0.95     |

## Mechanical Characteristics

|                  |                      |
|------------------|----------------------|
| Housing Material | Extruded Aluminium   |
| Surface Finish   | White powder coating |
| Optical Cover    | Opal Polycarbonate   |

## Initial Performance

|  |               |
|--|---------------|
| Source Luminous Flux                   | 5715 lm       |
| Source Efficacy                        | 157 lm/W      |
| Initial Luminaire Luminous Flux        | 4000 lm       |
| Initial Luminaire Efficacy             | 101 lm/W      |
| Initial Corr. Colour Temperature (CCT) | 4000 K        |
| Initial Color Rendering Index (CRI)    | >80 (Typ. 85) |
| Initial chromaticity                   | SDCM < 3      |

## Logistics

|                        |                   |
|------------------------|-------------------|
| Net weight per piece   | xxx kg            |
| Gross weight per piece | xx kg             |
| Volume                 | xx m <sup>3</sup> |
| Packing                | 1 pc per carton   |


## Over Time Performance

|                               |              |
|-------------------------------|--------------|
| Driver Service Life Time      | 50,000 hrs   |
| LED Median Useful Life L70B10 | 50,000 hours |

## Application Conditions

|                             |               |
|-----------------------------|---------------|
| Operating Temperature Range | -20 to +40 °C |
| Average Ambient Temperature | +25 °C        |

## Dimensional Drawing



ELMASCO INDUSTRIES S.A.

Head Office : 44 K. Palama, 14343 N. Chalkidona, Athens, Greece

Production Plant : Ag. Adrianos, 21100 Nafplio, Greece

Email: elmasco@elmasco.eu

Tel : +30 210 2583100

Fax: +30 210 2583107

