

LED SHOP LINE

CYF SYS2 SP52W7695LM865L170WH

PRODUCT DATA



821-569



General Information

Order Code	821-269
Product Description	CYF SYS2 SP52W7695LM865L170WH
Application	Shops, Offices, General Indoor Lighting
Installation	Ceiling Surfaced & Suspended with accessories
Accessories	Shop Line Suspension Kit
Luminaire type	Linear LED Luminaire with Opal Diffuser
Light Source	LED modules SMD Vossloh-Schwabe
Number of light sources	1 pc
Light Source Colour	6500K, cool daylight
Driver	Built-in Vossloh-Schwabe
Dimming	Not Dimmable
Energy Class	A++
Optical Risk	RG 0
Protection class	Class I
Ingress protection code	IP 20 [Finger-protected]
Mechanical impact protection code	IK03
Standards	2014/30/EU Electromagnetic Compatibility Directive 2014/35/EU Low Voltage Directive
CE mark	Yes
Warranty	5 years

Electrical Data

Input Power	57 W
Input voltage	220-240V
Input Frequency	50-60 Hz
Drive Current	500 mA
Power Factor	0.95

Mechanical Characteristics

Housing Material	Extruded Aluminium
Surface Finish	White powder coating
Optical Cover	Opal Polycarbonate

Initial Performance

Source Luminous Flux	7695 lm
Source Efficacy	148 lm/W
Initial Luminaire Luminous Flux	5387 lm
Initial Luminaire Efficacy	94 lm/W
Initial Corr. Colour Temperature (CCT)	4000 K
Initial Color Rendering Index (CRI)	>80 (Typ. 85)
Initial chromaticity	SDCM < 3

Logistics

Net weight per piece	xxx kg
Gross weight per piece	xx kg
Volume	xx m ³
Packing	1 pc per carton


Over Time Performance

Driver Service Life Time	50,000 hrs
LED Median Useful Life L70B10	50,000 hours

Application Conditions

Operating Temperature Range	-20 to +40 °C
Average Ambient Temperature	+25 °C

Dimensional Drawing



ELMASCO INDUSTRIES S.A.

Head Office : 44 K. Palama, 14343 N. Chalkidona, Athens, Greece

Production Plant : Ag. Adrianos, 21100 Nafplio, Greece

Email: elmasco@elmasco.eu

Tel : +30 210 2583100

Fax: +30 210 2583107

