



911-002



General Information

Order Code	911-002
Product Description	CYFELCO LS124.80IP200603528K30
Application	Accent lighting, light advertising, path lighting, task lighting, recreation lighting, under-cabinet lighting.
Installation	In Aluminium Profile
Light Source type	Flexible LED Strip
Light Source	LED SMDs 3528
Meters per Reel	5 m
Width	8 mm
Number of LEDs per meter	60 pcs/m
Light Source Colour	3000K, warm white
Flux per meter	>400 Lm
Dimming	Via suitable dimmer
CRI	>80
Energy Class	A+
Optical Risk	RG 0
Ingress protection code	IP 20 [Finger-protected]
Standards	2014/30/EU Electromagnetic Compatibility Directive 2014/35/EU Low Voltage Directive
CE mark	Yes
Warranty	5 years

Electrical Data

Input Power per meter	4.8 W
Input voltage	12 Vdc
Drive Current per meter	400 mA

Constructional Characteristics

LED Chip	Sanan
Phosphor	Mitsubishi or Intermatix
Gold Wire	Heraeus 99.9% purity
Lead Frame	100% copper
Copper Thickness	1oz >35µm
Coverlay	Double Layer Polyamide Film


Performance Data

Luminous Flux per meter	>400 lm
Luminous Efficacy	>83 lm/W
Chromaticity	SDCM < 5
Average Ambient Temperature	+25 °C

Logistics

Net weight per piece	0.125 kg
Gross weight per piece	xxx kg
Volume	0.0009 m ³
Packing	20 pcs per white box, 80 pcs per carton

Dimensional Drawing



ELMASCO INDUSTRIES S.A.

Head Office : 44 K. Palama, 14343 N. Chalkidona, Athens, Greece

Production Plant : Ag. Adrianos, 21100 Nafplio, Greece

Email: elmasco@elmasco.eu

Tel : +30 210 2583100

Fax : +30 210 2583107

